Under-threat alarm system (GAS)

The GAS system has been specially developed for use in armoured vehicles such as armoured limousines or cash-in-transit vehicles. The primary functions of GAS are a two-way intercom communication and an alarm that is triggered in the event of an attack on the vehicle. In addition, there is also an option of using GAS in conjunction with a beacon as a special signalling system.

Components	Mounting location	Functions
Operating unit GAS 614 or GAS 624	in the vehicle interior	 two-way intercom communication generation of an attack alarm control of a beacon generation of special signals
DKL 604 (1 or 2 pieces)	behind the radiator grille	 playback of voice traffic from the vehicle interior broadcast of the attack signal broadcast of the special signal
Mirror microphones (2 pieces)	exterior vehicle mirror	recording of the voice traffic/sounds surrounding the vehicle
Hands-free and/or rod microphone	e.g. near driver seat	recording of the voice traffic inside the vehicle
Push button or control unit	e.g. near driver seat	 activation of attack alarm as panic button activation of voice traffic activation of the beacon and special signal, if installed
Interior loudspeakers	use interior loudspeakers of the vehicle or order and install separately - near the driver seat	playback of the mirror microphone signals
Optional: beacon	on the vehicle roof	required in combination with the special acoustic signal to clear a path on the way to a location



Under-threat alarm system (GAS)

PRODUCT FEATURES:

- the amplifier circuit developed for special-purpose vehicles creates a very high sound pressure level, even for the attack alarm increased safety for vehicle occupants
- two-way intercom communication in closed, armoured vehicle possible with very clear voice transmission
- no intervention in the vehicle body required easy mounting, compact design of the components, discreet to install
- unique combination of intercom, special signal (pre-programmed with German homologation and US tones selectable) and attack alarm

For more information or a non-binding consultation, please contact us.

Operating unit GAS 614/624



The perfect balance between amplifier technology and the DKL 604 produces extremely high sound pressure for the special signal and alarm. The integrated intercom with outstanding voice quality allows communication with people on the outside of an armoured vehicle, e.g. by using the vehicle hands-free device and additional microphones installed in the exterior mirrors.

- powerful output stage (GAS 624) for attack alarm and special signals (many pre-programmed)
- homologation for German special signal according to DIN 14610 with two or even just one DKI 604
- integrated intercom
- extremely compact control unit

Homologation: (Germany and international)		
Acoustic according to TA32:	₩ 25071	
EMC according to ECE R-10:	E1) 10R-05 8888	

