# **COMET LED**

## **Fix mounting**



#### **PRODUCT FEATURES:**

- Fix mounting in accordance with DIN 14620, form B1
- Options:
  - Function monitoring (low or high)
  - Analogue or CAN447 version
- Colours: also available in blue, red, green and blue/amber

## Magnetic fixing



### **PRODUCT FEATURES:**

- With spiral cable and triple magnetic fixing
- Optimum bonding even on curved vehicle roofs
- Rubber-coated magnets to protect paintwork from scratches
- Tested at up to 250 km/h
- Colours: also available in blue, red, green and blue/amber

Both versions available with examination in accordance with ICAO type C. Further information can be found on page 61.



# **COMET LED**

## **Tube mounting**



Also available with examination in accordance with ICAO type C. Further information can be found on page 61.

### **PRODUCT FEATURES:**

- For fitting on a mounting tube in accordance with DIN 14620
- Impact-resistant housing base
- Options:

- Flexible (AF) or fixed tube (A)

• Colours: also available in blue, red and green

Technical data:	
Designation:	COMET LED
Voltage:	9-32V multi voltage
Flash frequency:	> 2 Hz
Average power consumption:	12 V: 1.5 A / 24 V: 0.75 A
Material:	Lamp dome: PC / socket: ASA
Type of protection:	IP5K4K/IPX9K
Homologation: (Germany and international)	
Light in accordance with ECE-R65:	TA1(E1)00 2872
EMC in accordance with ECE-R10:	E1)10R-04 5669

